

part	angle	Slic3r	RP3	HP (True)	HPA (60)	HPA (600)	HPB (60)	HPB (600)
adfoot	0	91.72	89.97	91.38	90.18	90.15	90.0	90.0
adfoot	90	91.06	90.18	90.55	90.47	90.47	90.23	90.23
bkwren	0	138.72	139.54	142.06	140.41	140.41	140.94	140.89
bkwren	90	134.55	134.26	135.74	135.74	134.11	134.57	134.11
cthang	0	128.09	127.88	125.96	125.62	125.62	125.62	125.62
cthang	90	126.9	125.49	130.52	130.52	127.32	130.27	130.02
dstop1	0	47.73	48.23	49.53	49.05	48.88	49.45	48.86
dstop1	90	47.08	46.98	47.16	46.9	46.9	46.9	46.9
dstop2	0	30.86	30.88	32.41	31.02	30.89	31.45	31.24
dstop2	90	29.11	28.37	28.4	28.07	27.9	27.91	27.9
flange	0	168.82	171.76	177.61	174.5	174.5	176.98	176.92
flange	90	172.83	174.46	177.43	175.58	175.58	176.02	175.92
hlatch	0	162.41	163.07	163.54	163.54	163.54	162.8	162.57
hlatch	90	160.02	160.11	169.58	162.66	162.66	167.22	166.96
holder	0	209.69	212.86	218.96	218.96	218.96	217.64	217.64
holder	90	216.08	213.16	220.0	220.0	220.0	219.2	219.2
ladder	0	23.96	24.46	24.47	24.14	24.14	24.15	24.15
ladder	90	23.66	22.93	25.08	23.23	23.19	23.97	23.95
nkhang	0	130.21	129.49	129.75	129.21	129.21	129.11	129.11
nkhang	90	138.86	141.25	144.99	144.99	144.99	144.55	144.26
runleg	0	120.54	124.27	125.01	123.59	123.59	123.97	123.68
runleg	90	111.19	116.49	132.47	132.47	132.47	129.93	129.29
tkwren	0	50.52	51.19	50.87	49.94	49.78	49.78	49.78
tkwren	90	53.76	55.44	55.44	55.06	55.06	55.06	55.06
unwren	0	37.75	38.38	39.6	38.39	38.39	39.1	38.64
unwren	90	32.95	33.49	35.58	32.81	32.8	34.6	34.48