

	Model	Deg	Slic3r			RP3			Scan			Alt			Hot 4					Hot 8						Hot 16						Hot inf					
0	Model	Deg	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)			
1	adfoot	0	97.5	87.2	1.2	90.0	27.5	1.2	141.0	1.9	56.9	101.8	2.6	15.3	96.8	3.8	9.6	8	7.6	91.6	7.8	3.2	9	1.8	89.8	15.1	1.2	11	-0.2	89.7	16.1	1.1	11	-0.3			
2	adfoot	90	96.3	83.0	0.9	90.2	14.5	1.0	144.6	1.5	60.9	102.6	2.1	16.0	93.7	4.0	5.3	10	3.9	91.1	7.9	2.1	11	1.0	90.3	13.6	1.2	12	0.1	90.3	13.6	1.2	12	0.1			
3	bkwren	0	137.8	96.0	0.5	139.5	50.0	0.6	314.4	1.9	185.2	203.9	2.1	69.1	155.2	4.0	17.4	21	12.6	145.3	7.9	6.9	22	5.4	142.5	15.3	3.9	22	3.4	142.4	16.4	3.8	22	3.3			
4	bkwren	90	134.6	106.4	0.8	134.3	6.7	0.9	210.1	1.9	83.5	144.8	2.1	12.0	136.6	4.0	3.2	11	1.7	134.2	6.7	0.9	12	-0.1	134.2	6.7	0.9	12	-0.1	134.2	6.7	0.9	12	-0.1			
5	cthang	0	126.4	118.2	2.1	127.9	100.0	1.9	240.1	2.1	127.1	153.6	2.2	32.3	129.4	3.9	6.0	23	2.4	126.5	6.4	2.7	24	0.1	126.1	10.9	2.1	24	-0.2	126.1	10.9	2.1	24	-0.2			
6	cthang	90	126.1	83.2	0.9	125.5	58.3	1.2	275.6	4.2	162.8	188.5	5.2	70.9	176.3	4.0	56.9	34	40.5	138.7	8.0	16.4	34	10.5	130.7	16.0	7.0	35	4.1	128.2	35.2	4.6	35	2.2			
7	dstop1	0	47.4	40.6	0.8	48.2	31.9	0.9	101.4	1.7	60.2	65.6	2.2	20.9	54.2	3.9	7.5	13	14.3	49.9	7.9	2.9	13	5.3	48.8	15.3	1.6	13	3.0	48.6	17.6	1.4	13	2.5			
8	dstop1	90	48.4	30.6	0.3	47.0	8.7	0.4	96.5	1.9	55.3	62.3	1.8	17.5	47.7	4.0	1.5	12	1.5	47.5	4.7	1.1	12	1.1	47.5	4.7	1.1	12	1.1	47.5	4.7	1.1	12	1.1			
9	dstop2	0	30.7	19.5	1.0	30.9	11.5	1.1	60.9	1.1	36.1	37.3	1.5	9.0	31.4	3.5	1.6	10	2.3	30.9	4.3	1.2	10	0.7	30.9	4.3	1.2	11	0.7	30.9	4.3	1.2	10	0.7			
10	dstop2	90	28.8	8.7	0.5	28.4	9.3	0.5	61.1	1.9	37.6	41.6	1.9	15.9	29.0	3.9	2.0	8	2.1	28.5	5.6	1.4	9	0.4	28.5	5.6	1.4	9	0.4	28.5	5.6	1.4	9	0.4			
11	flange	0	168.4	134.9	1.2	171.8	113.9	1.8	329.2	3.2	171.2	228.8	4.2	65.1	230.6	4.0	66.5	26	36.9	187.7	8.0	19.5	28	11.5	177.1	16.0	8.2	29	5.2	172.9	36.8	3.5	29	2.7			
12	flange	90	171.6	114.2	0.8	174.5	67.5	1.2	349.2	1.7	189.5	232.0	1.9	65.1	183.8	4.0	12.0	28	7.1	177.7	7.9	5.2	31	3.6	176.3	11.9	3.5	31	2.7	176.3	11.9	3.5	31	2.7			
13	hlatch	0	161.8	118.2	0.8	163.1	89.8	1.3	270.1	1.6	118.0	183.1	1.9	24.0	165.9	4.0	4.9	21	2.5	163.8	7.8	2.1	21	1.2	163.3	11.0	1.9	21	0.9	163.3	11.0	1.9	21	0.9			
14	hlatch	90	158.5	115.8	1.3	160.1	96.2	1.1	262.1	3.3	111.3	188.1	4.7	32.9	206.8	4.0	51.9	16	30.5	170.1	7.9	12.5	16	7.3	163.6	15.9	5.3	17	3.2	160.9	35.4	2.2	18	1.5			
15	ladder	0	23.9	18.7	1.3	24.5	18.8	1.6	63.3	2.0	45.8	49.8	2.9	31.1	31.1	4.0	9.6	25	30.1	25.5	7.9	2.8	28	6.7	25.1	12.2	2.4	28	5.0	25.1	12.2	2.4	28	5.0			
16	ladder	90	23.6	21.7	1.6	22.9	4.5	1.9	61.0	0.6	44.0	38.1	0.7	18.9	23.1	3.0	2.1	10	0.9	23.1	3.0	2.1	10	0.9	23.1	3.0	2.1	10	0.9	23.1	3.0	2.1	10	0.9			
17	nkhang	0	134.2	92.3	1.0	129.5	30.9	1.3	271.5	3.4	152.3	177.8	3.5	53.2	138.7	4.0	11.4	18	7.1	132.0	7.9	4.2	19	1.9	130.9	12.2	3.1	19	1.1	130.9	12.2	3.1	19	1.1			
18	nkhang	90	138.3	107.4	1.1	141.2	119.6	2.7	331.0	2.2	207.1	220.3	2.9	89.8	171.2	4.0	35.7	40	23.8	150.8	8.0	13.5	41	9.0	144.8	16.0	6.8	42	4.7	143.7	20.5	5.6	42	3.9			
19	runleg	0	156.5	143.2	2.9	181.9	64.8	3.4	402.4	1.3	246.4	249.7	1.4	79.1	186.0	4.0	8.6	53	18.8	183.0	7.7	5.2	54	16.9	183.0	9.0	5.2	55	16.9	183.0	9.0	5.2	55	16.9			
20	runleg	90	167.8	106.5	1.5	170.2	91.8	4.8	446.7	6.0	296.6	295.9	8.5	139.5	-	-	-	44	-	266.8	8.0	108.7	48	59.0	195.0	15.8	32.6	50	16.2	174.5	67.6	10.8	53	4.0			
21	tkwren	0	50.5	46.2	0.6	51.2	15.9	0.5	86.8	1.9	42.4	60.8	2.5	12.0	55.7	4.0	7.5	7	10.3	51.3	7.9	2.6	7	1.6	50.2	15.8	1.2	8	-0.6	50.2	15.8	1.2	8	-0.6			
22	tkwren	90	53.5	49.2	0.2	55.4	26.3	0.6	124.8	1.0	78.1	82.6	1.1	31.8	57.9	4.0	3.6	18	8.2	56.5	7.2	2.0	18	5.6	56.4	8.2	1.9	19	5.4	56.4	8.2	1.9	18	5.4			
23	unwren	0	37.1	36.8	0.9	38.4	15.8	1.4	108.8	1.0	80.8	68.4	1.4	36.2	39.5	4.0	3.0	22	6.5	39.3	5.2	2.7	22	5.9	39.3	5.2	2.7	22	5.9	39.3	5.2	2.7	22	5.9			
24	unwren	90	32.9	29.2	1.5	33.5	16.4	2.0	76.5	1.9	51.3	52.5	2.3	25.0	39.7	4.0	9.9	9	20.7	35.1	7.9	5.1	10	6.7	34.0	12.6	3.6	11	3.3	34.0	12.6	3.6	11	3.3			