

	Model	Deg	Slic3r			RP3			Scan			Alt			Hot 4					Hot 8						Hot 16						Hot inf					
0	Model	Deg	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)	Tfab	Tcool	Tair	Tcpu	Dif(%)			
1	adfoot	0	97.5	87.2	1.2	90.0	27.5	1.2	141.0	1.9	56.9	101.8	2.6	15.3	96.8	3.8	9.6	34	7.6	91.6	7.8	3.2	35	1.8	89.8	15.2	1.2	45	-0.2	89.7	32.3	1.0	51	-0.3			
2	adfoot	90	96.3	83.0	0.9	90.2	14.5	1.0	144.6	1.5	60.9	102.6	2.1	16.0	93.7	4.0	5.3	40	3.9	91.1	7.9	2.1	45	1.0	90.0	14.5	0.8	56	-0.2	90.0	14.5	0.8	56	-0.2			
3	bkwren	0	137.8	96.0	0.5	139.5	50.0	0.6	314.4	1.9	185.2	203.9	2.1	69.1	155.2	4.0	17.4	110	12.6	145.2	8.0	6.8	112	5.4	141.8	16.0	3.1	118	2.9	140.7	27.0	1.9	123	2.1			
4	bkwren	90	134.6	106.4	0.8	134.3	6.7	0.9	210.1	1.9	83.5	144.8	2.1	12.0	136.6	4.0	3.2	51	1.7	134.2	7.8	0.6	58	-0.1	134.2	7.8	0.6	59	-0.1	134.2	7.8	0.6	59	-0.1			
5	cthang	0	126.4	118.2	2.1	127.9	100.0	1.9	240.1	2.1	127.1	153.6	2.2	32.3	129.4	3.9	6.0	104	2.4	125.6	7.4	1.4	123	-0.6	125.6	7.4	1.4	124	-0.6	125.6	7.4	1.4	127	-0.6			
6	cthang	90	126.1	83.2	0.9	125.5	58.3	1.2	275.6	4.2	162.8	188.5	5.2	70.9	176.3	4.0	56.9	185	40.5	138.7	8.0	16.4	197	10.5	130.2	16.0	6.5	206	3.7	126.5	47.7	2.4	206	0.8			
7	dstop1	0	47.4	40.6	0.8	48.2	31.9	0.9	101.4	1.7	60.2	65.6	2.2	20.9	54.2	3.9	7.5	58	14.3	49.9	7.9	2.9	66	5.3	48.8	14.2	1.6	75	3.0	48.3	25.5	1.1	74	1.9			
8	dstop1	90	48.4	30.6	0.3	47.0	8.7	0.4	96.5	1.9	55.3	62.3	1.8	17.5	47.7	4.0	1.5	61	1.5	47.1	7.6	0.6	63	0.2	47.1	7.6	0.6	63	0.2	47.1	7.6	0.6	61	0.2			
9	dstop2	0	30.7	19.5	1.0	30.9	11.5	1.1	60.9	1.1	36.1	37.3	1.5	9.0	31.4	3.5	1.6	42	2.3	30.9	4.3	1.3	52	0.7	30.9	4.3	1.3	51	0.7	30.9	4.3	1.3	52	0.7			
10	dstop2	90	28.8	8.7	0.5	28.4	9.3	0.5	61.1	1.9	37.6	41.6	1.9	15.9	29.0	4.0	2.1	32	2.1	28.2	7.8	1.1	38	-0.7	28.2	7.8	1.1	38	-0.7	28.2	7.8	1.1	37	-0.7			
11	flange	0	168.4	134.9	1.2	171.8	113.9	1.8	329.2	3.2	171.2	228.8	4.2	65.1	230.6	4.0	66.5	138	36.9	187.7	8.0	19.5	149	11.5	177.1	16.0	8.2	163	5.2	171.4	62.7	1.7	172	1.8			
12	flange	90	171.6	114.2	0.8	174.5	67.5	1.2	349.2	1.7	189.5	232.0	1.9	65.1	183.8	4.0	12.0	144	7.1	177.7	7.9	5.2	155	3.6	175.3	15.9	2.5	171	2.2	174.9	20.0	2.0	176	1.9			
13	hlatch	0	161.8	118.2	0.8	163.1	89.8	1.3	270.1	1.6	118.0	183.1	1.9	24.0	165.9	4.0	4.9	99	2.5	163.7	7.8	1.9	107	1.2	163.1	15.6	1.5	112	0.8	162.9	21.9	1.4	112	0.7			
14	hlatch	90	158.5	115.8	1.3	160.1	96.2	1.1	262.1	3.3	111.3	188.1	4.7	32.9	206.8	4.0	51.9	76	30.5	170.1	7.9	12.5	79	7.3	163.6	15.9	5.3	85	3.2	160.2	63.9	1.2	102	1.1			
15	ladder	0	23.9	18.7	1.3	24.5	18.8	1.6	63.3	2.0	45.8	49.8	2.9	31.1	31.1	4.0	9.6	51	30.1	25.5	7.9	2.8	55	6.7	24.1	12.3	1.3	69	0.8	24.1	12.3	1.3	68	0.8			
16	ladder	90	23.6	21.7	1.6	22.9	4.5	1.9	61.0	0.6	44.0	38.1	0.7	18.9	22.9	3.2	1.9	44	0.0	22.8	4.2	1.8	51	-0.4	22.8	4.2	1.8	51	-0.4	22.8	4.2	1.8	52	-0.4			
17	nkhang	0	134.2	92.3	1.0	129.5	30.9	1.3	271.5	3.4	152.3	177.8	3.5	53.2	138.7	4.0	11.4	86	7.1	131.9	7.9	4.2	93	1.9	130.2	15.8	2.3	98	0.5	129.8	22.4	1.9	102	0.2			
18	nkhang	90	138.3	107.4	1.1	141.2	119.6	2.7	331.0	2.2	207.1	220.3	2.9	89.8	171.2	4.0	35.7	223	23.8	150.7	8.0	13.4	243	9.0	144.6	15.8	6.6	256	4.6	141.8	35.6	3.4	259	2.5			
19	runleg	0	156.5	143.2	2.9	181.9	64.8	3.4	402.4	1.3	246.4	249.7	1.4	79.1	186.0	4.0	8.6	257	18.8	181.9	8.0	3.6	283	16.2	181.2	11.0	3.3	298	15.8	181.2	11.0	3.3	292	15.8			
20	runleg	90	167.8	106.5	1.5	170.2	91.8	4.8	446.7	6.0	296.6	295.9	8.5	139.5	-	-	-	222	-	266.8	8.0	108.7	249	59.0	195.0	15.8	32.6	282	16.2	171.2	103.3	7.2	321	2.0			
21	tkwren	0	50.5	46.2	0.6	51.2	15.9	0.5	86.8	1.9	42.4	60.8	2.5	12.0	55.7	4.0	7.5	27	10.3	51.3	7.9	2.5	29	1.6	50.0	15.8	1.1	34	-1.0	49.8	29.3	0.8	35	-1.4			
22	tkwren	90	53.5	49.2	0.2	55.4	26.3	0.6	124.8	1.0	78.1	82.6	1.1	31.8	57.9	4.0	3.6	95	8.2	56.3	8.0	1.7	101	5.2	55.8	15.2	1.2	99	4.3	55.8	15.2	1.2	99	4.3			
23	unwren	0	37.1	36.8	0.9	38.4	15.8	1.4	108.8	1.0	80.8	68.4	1.4	36.2	39.4	4.0	2.8	113	6.2	38.7	7.9	2.0	123	4.3	38.6	9.1	2.0	122	4.0	38.6	9.1	2.0	124	4.0			
24	unwren	90	32.9	29.2	1.5	33.5	16.4	2.0	76.5	1.9	51.3	52.5	2.3	25.0	39.7	4.0	9.9	26	20.7	35.1	7.9	5.1	31	6.7	33.7	15.6	3.8	38	2.4	33.5	16.9	3.4	41	1.8			