

part	angle	Slic3r	RP3	HP (True	HPA (60)	HPA (600	HPB (60)	HPB (600)
adfoot	0	91,72	89,97	92,42	91,07	91,06	91,44	91,28
adfoot	90	91,06	90,18	91,09	90,27	90,27	90,58	90,23
bkwren	0	138,72	139,54	146,25	143,09	143,09	145,77	145,61
bkwren	90	134,55	134,26	135,74	134,26	134,26	134,26	134,26
cthang	0	128,09	127,88	125,96	125,62	125,62	125,62	125,62
cthang	90	126,9	125,49	139,75	-	-	139,01	138,89
dstop1	0	47,73	48,23	50,93	49,71	49,09	50,25	50,25
dstop1	90	47,08	46,98	47,16	46,96	46,96	46,96	46,96
dstop2	0	30,86	30,88	32,41	31,23	31,23	31,45	31,24
dstop2	90	29,11	28,37	28,4	28,07	27,9	27,9	27,9
flange	0	168,82	171,76	192,67	-	-	-	-
flange	90	172,83	174,46	180,13	-	-	-	-
hlatch	0	162,41	163,07	165,26	-	-	164,12	163,71
hlatch	90	160,02	160,11	175,78	-	-	173,52	172,79
holder	0	209,69	212,86	239,5	-	-	237,58	236,52
holder	90	216,08	213,16	240,91	-	-	239,18	239,04
ladder	0	23,96	24,46	24,47	24,17	24,17	24,16	24,16
ladder	90	23,66	22,93	25,08	23,42	23,36	23,97	23,95
nkhang	0	130,21	129,49	131,87	130,25	130,25	131,82	131,79
nkhang	90	138,86	141,25	154,01	-	-	-	-
runleg	0	120,54	124,27	125,01	124,2	123,81	123,92	123,92
runleg	90	111,19	116,49	151,14	-	-	149,57	148,97
tkwren	0	50,52	51,19	52,77	50,51	50,51	51,26	51,17
tkwren	90	53,76	55,44	56,52	56,15	56,07	56,09	56
unwren	0	37,75	38,38	39,6	-	-	38,98	38,98
unwren	90	32,95	33,49	35,58	33,02	33,02	34,6	34,6