

part	angle	Slic3r	RP3	HP (True)	HPA (60)	HPA (600)	HPB (60)	HPB (600)
adfoot	0	91.72	89.97	92.42	91.07	91.06	91.44	91.31
adfoot	90	91.06	90.18	91.09	90.27	90.27	90.58	90.23
bkwren	0	138.72	139.54	146.25	143.09	143.09	145.77	145.61
bkwren	90	134.55	134.26	135.74	134.79	134.26	134.26	134.26
cthang	0	128.09	127.88	125.96	125.62	125.62	125.62	125.62
cthang	90	126.9	125.49	139.75	139.75	139.75	139.01	138.89
dstop1	0	47.73	48.23	50.93	49.71	49.09	50.25	50.25
dstop1	90	47.08	46.98	47.16	46.96	46.96	46.96	46.96
dstop2	0	30.86	30.88	32.41	31.23	31.23	31.45	31.24
dstop2	90	29.11	28.37	28.4	28.07	27.9	27.9	27.9
flange	0	168.82	171.76	192.67	192.67	192.67	192.67	192.67
flange	90	172.83	174.46	180.13	180.13	180.13	180.13	180.13
hlatch	0	162.41	163.07	165.26	165.26	165.26	164.12	163.71
hlatch	90	160.02	160.11	175.78	175.78	175.78	173.52	172.79
holder	0	209.69	212.86	239.5	239.5	239.5	237.65	236.52
holder	90	216.08	213.16	240.91	240.91	240.91	239.18	239.04
ladder	0	23.96	24.46	24.47	24.47	24.47	24.16	24.16
ladder	90	23.66	22.93	25.08	25.08	23.36	23.97	23.95
nkhang	0	130.21	129.49	131.87	130.25	130.25	131.82	131.79
nkhang	90	138.86	141.25	154.01	154.01	154.01	154.01	154.01
runleg	0	120.54	124.27	125.01	125.01	123.81	123.92	123.92
runleg	90	111.19	116.49	151.14	151.14	151.14	149.57	148.97
tkwren	0	50.52	51.19	52.77	50.51	50.51	51.26	51.17
tkwren	90	53.76	55.44	56.52	56.15	56.07	56.09	56.0
unwren	0	37.75	38.38	39.6	39.6	39.6	38.98	38.98
unwren	90	32.95	33.49	35.58	33.02	33.02	34.6	34.6